

Print Server with 1 USB Port

Product Overview

The LevelOne FPS-1032 print server is an ideal network printing solution for small offices, home offices, schools and other businesses that require printer sharing over the same network. This print server is equipped with a 10/100Mbps auto-sensing Ethernet port and a USB 2.0 port that connected to USB printer.

Multi OS and Network Printing Protocol Support

The FPS-1032 1-port USB print server supports Windows ME/ 2000 and XP operating systems as well as Mac OS 8.1 and higher, UNIX/Linux and Netware (Bindery/NDS).

Network Protocol supported includes TCP/IP, IPX, NetBEUI, AppleTalk, LPR and SMB over TCP/IP for flexible use with different network clients connected to the same office network. The FPS-1032 also includes Internet Printing Protocol (IPP) support and Windows Print Monitor Technology to monitor printing jobs received.

Easy Installation Wizard

The LevelOne FPS-1032 is easily configurable using a Web Browser or Windows based configuration program included with the CD-ROM. The print server is easily managed through a Web based user interface and the firmware is upgradeable through TFTP, the windows set-up program or the Web based user interface.



FPS-1032

Key Features

- USB print server for network print sharing
- High-speed USB 2.0 interface
- Fast Ethernet network connectivity
- USB print server for network print sharing
- Easy set-up wizard included
- Web based user interface
- Support multiple operating systems
- Support multiple network printing protocols

Technical Specification

Device Specifications

Standards Compliance

- IEEE 802.3 10Mbps Ethernet
- IEEE 802.3u 100Mbps Fast Ethernet

Network Interface

- 1x 10/100Mbps Auto-sensing RJ-45 port
- 1x USB 2.0 Auto-sensing port
- DHCP Client

Operating System Support

- Windows ME, 2000, XP, Vista
- Mac OS 8.1 or higher
- UNIX/Linux
- NetWare (Bindery/NDS)

Network Print Protocol Support

- TCP/IP, IPX, NetBEUI, AppleTalk, LPR, SMB over TCP/IP, Internet Printing Protocol (IPP), RAW

Software Upgradeable

- Web interface
- Windows-based Setup Program
- TFTP

Device Management

- Web-based user interface
- Windows-based Setup Program
- SNMP & HP Web JetAdmin Support

Physical Specifications

LEDs

Power/Status, Link, Activity

Power Supply

3.3V, 2A

Dimension

73.16mm (L) x 64.75mm (W) x 28.39mm (H)

Weight

56g


Operating Temperature and Humidity

Operating: 0°C ~ 50°C @ 0% ~ 70% (non-condensing)
Storage: -5°C ~ 65°C @ 0%~ 80% (non-condensing)

EMI Certifications

CE, FCC Class B

Product Diagram



Order Information

FPS-1032: Print Server w/ 1 USB Port

Package Content

- FPS-1032
- Power Adapter
- CD Manual/Driver/Utility
- Quick Installation Guide